

### EGGER OSB / 4 TOP, BAZ - 9.1 - 566

Format	Decklage	Besonderheit	Stärke
2500 x 1250 mm	ungeschliffen	stumpf	15 mm
2650 x 1250 mm	"	"	15 mm
2800 x 1250 mm	"	"	15 mm
3000 x 1250 mm	"	"	15 mm
2500 x 1250 mm	ungeschliffen	stumpf	22 mm
2500 x 675 mm	ungeschliffen	4-seitig Nut + Feder	15 mm
	"	"	18 mm
	"	"	22 mm
	"	"	25 mm
	"	"	30 mm
2500 x 1250 mm	ungeschliffen	4-seitig Nut + Feder	22 mm

### EGGER OSB / 3 E0 - EN 300, 100 % formaldehydfrei verleimt

Format	Decklage	Besonderheit	Stärke
2500 x 1250 mm	ungeschliffen	stumpf	10 mm
	"	"	12 mm
	"	"	15 mm
	"	"	18 mm
	"	"	22 mm
	"	"	25 mm
2500 x 675 mm	ungeschliffen	4-seitig Nut + Feder	12 mm
	"	"	15 mm
	"	"	18 mm
	"	"	22 mm
	"	"	25 mm
2500 x 1250 mm	ungeschliffen	4-seitig Nut + Feder	22 mm

### EGGER DHF bauaufsichtlich zugelassen: Z-9.1 - 454

Format	Decklage	Besonderheit	Stärke
2500 x 612 mm		4-seitig Nut + Feder	20 mm
2500 x 675 mm		"	15 mm